Technical Data Sheet



Silane LS-AS312

Description:

Chemical Name: 3-(1,3-dimethylbutylidene)aminopropylmethyldiethoxysilane

Typical Technical Properties:

Appearance:Pale yellow to brown transparent liquid Refractive Index (25°C): 1.437 Purity(%): 95 Density(25°C, g/cm³): 0.93

Applications:

This compound serves as a silane coupling agent and is primarily used in industries such as adhesives, coatings, inks, rubber, casting, glass fiber, cables, textiles, plastics, fillers, and surface treatments.

Package & Storage:

In 200L drum, 1000L IBC.

Keep in cool, dry and ventilated place. Keep away from sunlight and fire sources. Keep away from acid and alkali. Keep in unopened containers.

Storage beyond the shelf life does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Nanjing Silfluo New Material Co., Ltd.

Web: www.silfluosilicone.com Email: inquiry@silfluo.com

The offered information of this docs is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are fully satisfactory for end use. Suggestions of use shall not be taken as inducements to infringe any patent. Please confirm with us prior to any problems.